

INTERACTIVE TOOLS

ActiView Visual Presenters enable printed materials and objects to be viewed and shared with the entire class. This offers opportunities for collaboration in the classroom as it facilitates the sharing of information and work, as well as enabling students to engage collectively with 3D objects. Uniquely integrated with ActiVInspire software, images can be annotated over and saved in flipchart format or images and video can be automatically inserted into flip chart pages.

MINIMUM COMPUTER REQUIREMENTS

Operating Systems	Windows XP SP2 and above (XP/Vista/7) Mac OSX 10.4.11 – 10.6.1 (Tiger/Leopard/Snow Leopard) Linux Ubuntu 9.04, 9.10; Debian (ActiView 322 only)
PC	Pentium 4 – 1 GHz processor (800MHz for Vista), 512 MB of RAM, 1024x768 resolution, 1.5 GB of Free Disk Space
Mac	Intel Processors (Universal Binary), 512 MB of RAM, 1024x768 resolution, 3.0 GB of Free Disk Space



ActiView 122



ActiView 322



ActiView 522

SPECIFICATIONS

Model	ActiView 122	ActiView 322	ActiView 522
Output Resolution	XGA (1024 x 768) SXGA (1280 x 1024) UXGA (1600 x 1200)	XGA (1024 x 768) SXGA (1280 x 1024) WXGA (1280 x 800)	XGA (1024 x 768) SXGA (1280 x 1024) UXGA (1600 x 1200) HDTV 1080p, 720p
Frame Rate	30 fps maximum	30 fps maximum	30 fps maximum
Zoom Capacity	6X Mechanical Zoom	6X Mechanical and Digital Zoom	6X Mechanical and Optical Zoom
Capture Area	400mm x 300mm (15.7in x 11.8in)	350mm x 280mm (14in x 11in)	406.4mm x 304.8mm (16in x 12in)
Lamp Type	Integrated LED	Cold cathode	Cold cathode
Lamp Life	Over 20,000 hours	Up to 20,000 hours	Up to 20,000 hours
Number of Lamps	One integrated	One light on independent gooseneck	Two lights on independent goosenecks
Power Supply	Built-in; 100-240 VAC, auto switching	Built-in; 100-240 VAC, auto switching	Built-in; 100-240 VAC, auto switching
VGA Pass Thru Max Display Mode	Not available	Active pass-through, up to UXGA 60 Hz; VGA In and VGA Out	Yes, active pass-through, up to UXGA 60 Hz; VGA In and VGA Out
VGA In	Not available	1 In	1 In
VGA Out	Not available	2 ports to projector/computer and to monitor for VGA pass-thru	2 ports to projector/computer and to monitor for VGA pass-thru
USB	USB 2.0 High Speed (up to 480 Mbps) powered	USB 2.0 High Speed (up to 480 Mbps)	USB 2.0 High Speed (up to 480 Mbps)

CONTINUED ON NEXT PAGE

ActiView SS 05/12 V1.4

©2012 Promethean Limited. All rights reserved. Promethean Ltd. is owner of a number of trademarks in several jurisdictions across the world. Any third-party product and company names are mentioned for identification purposes only and may be trademarks of their respective owners. ¹Applicable Terms and Conditions for warranty and support available at www.PrometheanWorld.com/ActiVInspire. All dimensions +/- 5mm (0.2in). All weights +/- 0.9kg (2lb). Product Specifications are subject to change without notice. www.PrometheanWorld.com

SPECIFICATIONS (CONTINUED)

Composite Video Out	Not available	RCA Jack, NTSC/PAL	RCA Jack, NTSC/PAL
HDMI	Not available	Not available	HDTV 1080P, 720P
RS232	Not available	3.5mm RS232	RS232
Microphone	Yes	Not available	Yes
Internal Memory	Not available	120 JPEG Images	240 JPEG images
Image Capture	Capture images to the computer via USB connection;	Capture images to internal memory or to the computer via USB connection	Supports SDHC cards up to 32GB Capture images to internal memory or to the computer via USB connection
Image Rotation	Full screen image rotation from 0 to 180 degrees	Full screen image rotation from 0 to 90, 180 to 270 degrees	Full screen image rotation from 0 to 90, 180 to 270 degrees
Video Capture	Video recording to computer with various compression codecs	Video recording to computer with various compression codecs	Video recording to computer or built-in memory with various compression codecs
Pan	Not available	Automatically zoom from full page to separate quadrants	Automatically zoom from full page to separate quadrants
Security	Kensington lock slot available; VESA standard to mount to a surface	Auto Erase Mode (option to automatically erase internal memory during power down); Kensington lock slot available; VESA standard to mount to a surface	Auto Erase Mode (option to automatically erase internal memory during power down); Kensington lock slot available; VESA standard to mount to a surface
Certifications/Compliance	FCC-EMI, CE-EMC, RoHS, and WEEE	FCC-EMI, cUL, CE-EMC, CE-LVD, RoHS, and WEEE	FCC-EMI, cUL, CE-EMC, CE-LVD, RoHS, and WEEE
Weight	1kg (2.2lbs)	2.3kg (5lbs)	2.3kg (5lbs)
Dimension	434.3cm x 106.7cm x 309mm (17.1in x 4.2in x 12.2in) (LxWxH)	460cm x 220cm x 400cm (18.1in x 5.5in x 15.7in) (LxWxH)	431.8cm x 210.8cm x 558.8mm (17in x 8.3in x 22in) (LxWxH)
Languages	Chinese (Traditional & Simplified), Dutch, English, Italian, Brazilian Portuguese, German, Finnish, French, Polish, Danish, Russian, Portuguese, Spanish and Swedish	Chinese (Traditional & Simplified), Dutch, English, Italian, Brazilian Portuguese, German, Finnish, French, Polish, Danish, Russian, Portuguese, Spanish and Swedish	Chinese (Traditional & Simplified), Dutch, English, Italian, Brazilian Portuguese, German, Finnish, French, Polish, Danish, Russian, Portuguese, Spanish and Swedish
Packed Contents List	10 ft USB cable, microscope adapter, CD and Quick Start Guide	US/UK/EMEA Power leads, VGA, USB, and Composite video cables, microscope adapter, remote control, CD, Quick Start Guide and User Manual	US/UK/EMEA Power leads, VGA, USB, extender and microscope adapters (x3), remote control, CD and Quick Start Guide

WARRANTY AND SUPPORT[†]

Warranty	For Promethean Warranty Information please visit: www.PrometheanWorld.com/Warranty
Support	Online Support for all Promethean Products available from: www.PrometheanKB.com

ActiView SS 05/12 V1.4

©2012 Promethean Limited. All rights reserved. Promethean Ltd. is owner of a number of trademarks in several jurisdictions across the world. Any third-party product and company names are mentioned for identification purposes only and may be trademarks of their respective owners. [†]Applicable Terms and Conditions for warranty and support available at www.PrometheanWorld.com/ActiViewCare. All dimensions +/- 5mm (0.2in). All weights +/- 0.9kg (2lb). Product Specifications are subject to change without notice. www.PrometheanWorld.com